

20V/500mA, 0.8uA Ultra-Low Power High Precision Linear Regulator

1 Description

The CN8501 is an ultra-low quiescent power, low dropout linear regulator fabricated in CMOS process. The regulator consumes about 0.8uA and 0.01uA (typical) after enable/shutdown. Built-in enable control, output discharge, short circuit protection, and thermal shutdown are available in SOT89-3, SOT23-5, and SOT23-3 packages.

2 Features

- Ultra-low Quiescent Current: 0.8μA(VIN=12V)
- Shutdown Current: 0.01uA
- Input Range: 2.8V-20V
- Output Range: 1.8V-5V (0.1V interval)
- High Precision: ±2%
- Maximum Output Current: 500mA
- Enabling Control
- Output Discharge
- Output Short Circuit Protection
- Thermal Shutdown

3 Applications

- Cell Phone
- Battery powered equipment
- Wireless Telephones,
Wireless Communication Equipment
- Camera Recorder
- Portable Audio-Visual Equipment
- PDA (Personal Digital Assistant)

4 Ordering Information

Product Number	Package	Quantity/Tape
CN8501MXXXOGR	SOT89-3	1000/Tape
CN8501MXXXAOGR	SOT89-3	1000/Tape
CN8501MXXXTCR	SOT23-5	3000/Tape
CN8501MXXXTGR	SOT23-3	3000/Tape
CN8501MXXXTCRA	SOT23-5	3000/Tape


5 Marking

Product Number	Marking*
CN8501MXXXAOGR	01MXXXA YYWW
CN8501MXXXOGR	01MXXX YYWW
CN8501MXXXTCR	MXXX YYWW
CN8501MXXXTGR	MXXX YYWW
CN8501MXXXTCRA	MXXXA YYWW


Note: YY=Year WW=Week; 8501MXXX=Product Name, XXX= Output Voltage

Green (RoHS & HF): CHIPNORTH defines "Green" to mean Pb-Free (RoHS compatible) and free of halogen substances. If you have additional comments or questions, please contact your CHIPNORTH representative directly.
Moisture sensitivity level(MSL):3


6 Pinout



7 Typical Application



8 Block Diagram



9 Pin Descriptions

CN8501M XXXOGR	CN8501M XXXAOG	CN8501M XXXTCR	CN8501M XXXTCRA	CN8501M XXXTGR	Pin Name	Descriptions
SOT89-3	SOT89-3	SOT23-5	SOT23-5	SOT23-3		
/	/	3	/	/	CE	Enable pin
2	1	2	2	1	GND	Ground
		4	3、4		NC	No Connection
3	2	1	1	3	VIN	Power supply input
1	3	5	5	2	VOUT	Voltage output

10 Specifications

10.1 Absolute Maximum Ratings

Parameter	Symbol	Value	Units
Supply Input Voltage	V_{IN}	28	V
Output Voltage	V_{OUT}	-0.3 ~ 7	V
CE Voltage	V_{CE}	-0.3 ~ 28	V
Operating Junction Temperature Range	T_{OPR}	-40 ~ 150	°C
Soldering Temperature	T_{LEAD}	260(soldering, 10s)	°C
Storage Temperature Range	T_{STG}	-55 ~ 150	°C

Note1: Stress exceeds these ratings listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Expose to absolute-maximum-rated conditions for extended periods may affect device reliability.

10.2 ESD Ratings

Discharge mode	Standardize	Value	Units
HBM	ESDA/JEDEC JS-001-2017	±4000	V
CDM	ESDA/JEDEC JS-002-2018	±2000	V

10.3 Recommended Operating Range

Parameter	Symbol	Min.	Max.	Units
Input Voltage Range	V_{IN}	$V_{OUT}+1$	20	V
Output Voltage Range	V_{OUT}	1.8	5	V
Operating Ambient Temperature Range	T_A	-40	85	°C
Output Current	I_{OUT}	0	500	mA
Input Capacitor	C_{IN}	1		μF
Output Capacitor	C_{OUT}	1		μF

10.4 Thermal Information

Parameter		CN8501					Units
		OGR [SOT89-3]	AOGR [SOT89-3]	TCR [SOT23-5]	TCRA [SOT23-5]	TGR [SOT23-3]	
$R_{\theta JA}$	Junction to ambient	72.5	131.7	195.7	195.7	297.3	°C/W
$R_{\theta JC(top)}$	Junction to case(top)	121.4	65.8	88.2	88.2	128.5	°C/W
$R_{\theta JB}$	Junction to Board	37.3	32.4	40.7	40.7	91.7	°C/W

10.5 Electrical Characteristics

CN8501M050

(VIN=VOUT+1V, CIN=1μF, COUT=1μF, TA=25°C, unless otherwise specified.)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Output Voltage	V _{OUT}	I _{OUT} = 30mA	4.9	5	5.1	V
Maximum Output Current	I _{OUTMAX}	V _{IN} = V _{OUT} + 1V	500			mA
Load regulation	ΔV _{OUT}	1mA ≤ I _{OUT} ≤ 500mA		15	23	mV
Dropout voltage	V _{DIF1}	I _{OUT} = 100mA		100	203	mV
Input Quiescent Current	I _Q	V _{IN} = 6V		0.5	1	μA
Shutdown Current	I _{SD}	V _{CE} = 0V		0.01		μA
Line regulation	$\frac{\Delta V_{OUT}}{\Delta V_{IN} * V_{OUT}}$	I _{OUT} = 0mA ΔV _{OUT} +1V ≤ ΔV _{IN} ≤ 18V		0.003	0.36	%/V
CE Rising Threshold	V _{CEH}	On, output voltage stabilized	1.3			V
CE Falling Threshold	V _{CEL}	Off, output voltage is 0			0.4	V
Short-Circuit Current	I _{SHORT}	V _{IN} = V _{OUT} + 1V, V _{CE} = V _{IN} V _{OUT} = 0V		50		mA
Current Limiting	I _{limit}	V _{OUT} = V _{OUT(E)} × 0.95 V _{IN} = V _{OUT} + 2V	500	800		mA
Load Capacitor Discharge Resistance	R _{DCHG}	V _{CE} = V _{SS} , V _{OUT} = V _{OUT}		500		Ω
Thermal Shutdown Temperature	OTP			160		°C
Thermal Shutdown Hysteresis	OTP_HYS			30		°C

CN8501M040

(VIN=VOUT+1V, CIN=1μF, COUT=1μF, TA=25°C, unless otherwise specified.)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Output Voltage	V _{OUT}	I _{OUT} = 30mA	3.92	4	4.08	V
Maximum Output Current	I _{OUTMAX}	V _{IN} = V _{OUT} + 1V	500			mA
Load regulation	ΔV _{OUT}	1mA ≤ I _{OUT} ≤ 500mA		10	23	mV
Dropout voltage	V _{DIF1}	I _{OUT} = 100mA		110	203	mV
Input Quiescent Current	I _Q	V _{IN} = 5V		0.5	0.8	μA
		V _{IN} = 7.5V		0.7	1	μA
Shutdown Current	I _{SD}	V _{CE} = 0V		0.01		μA
Line regulation	$\frac{\Delta V_{OUT}}{\Delta V_{IN} * V_{OUT}}$	I _{OUT} = 0mA ΔV _{OUT} +1V ≤ ΔV _{IN} ≤ 18V		0.01	0.55	%/V
CE Rising Threshold	V _{CEH}	On, output voltage stabilized	1.3			V
CE Falling Threshold	V _{CEL}	Off, output voltage is 0			0.4	V
Short-Circuit Current	I _{SHORT}	V _{IN} = V _{OUT} + 1V, V _{CE} = V _{IN} V _{OUT} = 0V		50		mA
Current Limiting	I _{limit}	V _{OUT} = V _{OUT(E)} X 0.95 V _{IN} = V _{OUT} + 2V	500	800		mA
Load Capacitor Discharge Resistance	R _{DCHG}	V _{CE} = V _{SS} , V _{OUT} = V _{OUT}		500		Ω
Thermal Shutdown Temperature	OTP			160		°C
Thermal Shutdown Hysteresis	OTP_HYS			30		°C

CN8501M033

(VIN=VOUT+1V, CIN=1μF, COUT=1μF, TA=25°C, unless otherwise specified.)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Output Voltage	V _{OUT}	I _{OUT} = 30mA	3.234	3.3	3.366	V
Maximum Output Current	I _{OUTMAX}	V _{IN} = V _{OUT} +1V	500			mA
Load regulation	ΔV _{OUT}	1mA ≤ I _{OUT} ≤ 500mA		10	23	mV
Dropout voltage	V _{DIF1}	I _{OUT} = 100mA		120	203	mV
Input Quiescent Current	I _Q	V _{IN} = 5V		0.5	0.8	μA
Shutdown Current	I _{SD}	V _{CE} = 0V		0.01		μA
Line regulation	$\frac{\Delta V_{OUT}}{\Delta V_{IN} * V_{OUT}}$	I _{OUT} = 10mA ΔV _{OUT} +1V ≤ ΔV _{IN} ≤ 18V		0.01	0.55	%/V
CE Rising Threshold	V _{CEH}	On, output voltage stabilized	1.3			V
CE Falling Threshold	V _{CEL}	Off, output voltage is 0			0.4	V
Short-Circuit Current	I _{SHORT}	V _{IN} = V _{OUT} +1V, V _{CE} = V _{IN} V _{OUT} = 0V		50		mA
Current Limiting	I _{limit}	V _{OUT} = V _{OUT(E)} X 0.95 V _{IN} = V _{OUT} +2V	500	800		mA
Load Capacitor Discharge Resistance	R _{DCHG}	V _{CE} = V _{SS} , V _{OUT} = V _{OUT}		500		Ω
Thermal Shutdown Temperature	OTP			160		°C
Thermal Shutdown Hysteresis	OTP_HYS			30		°C

Notes:


 *1. V_{OUT(E)}: output voltage when V_{IN} = V_{OUT} + 1V, I_{OUT} = 1mA.







 *2. V_{DROP}=V_{IN}-(V_{OUT_REG}*0.98), V_{OUT_REG} is the output voltage when V_{IN} = V_{OUT} + 1.0V and I_{OUT} = 100mA. V_{IN} is the input voltage, and when the input voltage is gradually reduced, the output voltage becomes 98% of V_{OUT_REG}.


 *3. I_{LIMIT}: Output current when V_{IN} = V_{OUT} + 1V and V_{OUT} = 0.95 X V_{OUT(E)}.

10.6 Characteristics Curve


(VIN=12V, CIN=1uF, COUT= 1uF, TA=25°C, unless otherwise specified.)








Short circuit protection



Short circuit recovery


11 Package Information

SOT89-3




Size Symbol	Min(mm)	Max(mm)
A	4.40	4.60
A1	1.65	1.75
A2	2.95	3.05
A3	0.35	0.45
A4	0.43	0.53
A5	0.35	0.45
B	2.40	2.60
B1	4.05	4.25
B2	0.82	0.83
B3	0.82	0.83
C	1.40	1.60
C1	0.35	0.45
θ	6°TYP4	
θ1	3°TYP4	
θ2	6°TYP4	
θ3	3°TYP4	

SOT23-5



Size Symbol	Min(mm)	Max(mm)
A	2.82	3.02
e	0.95(BSC)	
b	0.27	0.35
B	1.50	1.70
B1	2.60	3.00
C	1.05	1.15
C1	0.03	0.15
C2	0.135	0.23
L	0.35	0.55
θ	0°	8°

SOT23-3



Size Symbol	Min(mm)	Typ(mm)	Max(mm)
A	2.70	2.90	3.10
A1	1.70	1.90	2.10
A2			0.60
e	0.85	0.95	1.05
b	0.30	0.40	0.50
B	1.50	1.60	1.80
B1	2.60	2.80	3.00
C	1.00	1.10	1.20
C1			0.10
C2	0.02		0.08
L1	0.20		0.55
L2		0.60	
θ	0°		15°

12 Important Statement

Chipnorth Electronic Technology (Nanjing) Co., Ltd. and its subsidiaries reserve the right to make modifications, improvements, corrections, or other changes to this document and to any of the products described herein at any time without notice. Chipnorth Electronic Technology (Nanjing) Co., Ltd. disclaims any liability arising out of the use of this document or any of the products described herein; Chipnorth Electronic Technology (Nanjing) Co., Ltd. does not transfer any license to its patents or trademarks or other rights. Any customer or user using this document or any of the products described herein assumes all risk and agrees to hold harmless Chipnorth Electronic Technology (Nanjing) Co., Ltd. and all companies whose products are displayed on Chipnorth Electronic Technology (Nanjing) Co., Ltd.

Chipnorth Electronic Technology (Nanjing) Co., Ltd. makes no warranty and assumes no responsibility for any products purchased through unauthorized sales channels. In the event that a customer purchases or uses a product from Chipnorth Electronic Technology (Nanjing) Co., Ltd. for any unintended or unauthorized use, the customer shall indemnify and hold harmless Chipnorth Electronic Technology (Nanjing) Co., Ltd. and its representatives from and against all claims, damages, and attorney's fees arising from any personal injury or death, directly or indirectly, arising out of or in connection with such purchase or use.